

# ISGUS Terminal Series IT 4100 IT 4110



IT 4100



IT 4110



## IT 4100 and IT 4110 for Access Control

- » Terminals for access control with contact free identification
- » Operation via transponder with reading distance of 3 - 5 cm
- » Door opening via integrated electronic relay or via external door control (Device I/O Master / Slave) in the secured area
- » Status display and booking acknowledgement via LED and acoustic signal

- » Door opening function also in offline mode via system number check
- » 2 inputs
- » Anti-tamper alarm device via case contact
- » Connection to terminal series IT 8xxx, ACM 40xx or ACM 400 as sub terminal
- » Easy and flexible installation
- » Suitable for outdoor environments
- » Multi-company feature for up to 10 different companies

## IT 4100 Long Range

- » The access reader IT 4100 Long Range enables reading distances of up to 5 m
- » Active transponder, also available as combined transponder with Hitag 1, ISGUS Prox or EM4102



IT 4100 Long Range

# Technical Information **IT 4100** Terminal **IT 4110**



**IT 4110**

**IT 4100**

## Badge reader systems

- » ISGUS-Prox
- » Hitag
- » LEGIC
- » Mifare
- » PAC
- » HID

## Voltage

- » 9 - 15 V AC or 12 - 24 V DC
- » SELV-circuits only

## Current consumption

- » Approx. 1,5 W (depending on reader type)

## Protection type

- » IP 65 front side

## Protection class

- » III / EN 60950

## Environment

- » No direct sunlight
- » Ambient temperature: -10° C to +55° C

## Rel. humidity

- » max. 85 % (non condensing))

## Data communication

- » Serial
- » RS 485, 2-wire
- » galvanically isolated

## Weight

- » Approx. 0,15 kg

## Dimensions

- » Height: 114 mm
- » Width: 75 mm
- » Depth: 23 mm

